


absolute - stone collection




bianco



grigio




avorio










rosso







sizes and specifications

Sizes (mm):	Finishes:	Colours:	Special Pieces:	Sizes (mm):	Finishes:	Colours:
750 x 1500 x 10	Polished / Natural	All	Skirting Tile	90 x 750 x 10	Polished / Natural	All
750 x 750 x 10	Polished / Natural	All	Step Tile (Special order only)	375 x 100 x 10 to 375 x 150 x 10	Polished / Natural	All
375 x 750 x 10	Polished / Natural	All				



technical specifications

	technical data	standard	requirement	collection value
	sides	EN ISO 10545-2	± 0.6% max	conforms
	thickness	EN ISO 10545-2	± 5.0% max	±5%
	straightness of sides	EN ISO 10545-2	± 0.5% max	± 0.1%
	rectangularity	EN ISO 10545-2	± 0.6% max	± 0.1%
	surface flatness	EN ISO 10545-2	± 0.5% max	± 0.1%
	water absorption	EN ISO 10545-3	< 0.5% max	0.02 - 0.07%
	bending resistance	EN ISO 10545-5	≥ 35 N/mm ²	50 N/mm ²

	technical data	standard	requirement	collection value
	abrasion resistance	EN ISO 10545-6	≤ 175mm ³	140mm ³
	coefficient of linear thermal expansion	EN ISO 10545-8	< 9 MK ⁻¹	6.2x10 ⁻⁶ °C ⁻¹
	thermal shock resistance	EN ISO 10545-9	no visible defects	Resistant
	frost resistance	EN ISO 10545-12	no visible defects or cracks	Resistant
	chemical resistance	EN ISO 10545-13	no visible changes to surface	conforms
	stains resistance	EN ISO 10545-14	no permanent staining	class 5 conforms
	slip resistance	DIN 51130 RAMP TEST	R9-R13	R9 Natural